
Audiometer MA 25 Light and independent for basic screening



- New features combined with a fresh design
- Air Conduction with 11 frequencies from 125 Hz to 8000 Hz
- Customize the frequencies according to your own needs
- ullet Intensities from -10 dB $_{\rm HL}$ to 100 dB $_{\rm HL}$ in steps of 5 or 1 dB
- Pure, warble and pulse tone
- Independent with battery or eco-friendly with power supply
- MA 25e with automatic tests according to Hughson-Westlake



Audiometer MA 25

Easy and mobile basic screening audiometry

The MA 25 is the ideal audiometer wherever quick basic hearing screening evaluation is needed. It is our smallest and lightest independent audiometer.

Full range of test options

The MA 25 offers a full range of testing opportunities. Frequencies range from 125 Hz to 8000 Hz and signal intensities run from -10 dB $_{\rm HL}$ to 100 dB $_{\rm HL}$. Pure, pulse and warble tone make it complete.

Easy to use

At a glance the short guide will show you the easy handling of the MA 25.

Reliable engineering

Because it is portable, the MA 25 has been engineered reliable, light and robust at the same time. User-friendly knobs make adjusting frequency and hearing levels easy and comfortable.

Batteries or power supply

The MA 25 can be operated with 3 standard AA batteries or eco-friendly with a medically approved external power supply.

Extended functions

The MA 25e extends the MA 25 functionalities with an automatic test according to Hughson-Westlake. Parameters can easily be adapted to your personal preferences. The Talk Forward function makes the MA 25e easy to work with, particularly in sound booth installations.



MA 25 function buttons

Technical Data

Test signals: Pure, pulse and warble tone

Test frequencies Hz: 125, 250, 500, 750, 1000, 1500,

2000, 3000, 4000, 6000, 8000

Level steps: 5 or 1 dB

Dynamic range: $-10 \text{ dB}_{HL} - 100 \text{ dB}_{HL}$

70 dB $_{\rm HL}$ at 0.125 kHz, 90 dB $_{\rm HI}$ at 0.25 and 8 kHz

Audiometer Class: Class 4 according to EN 60 645-1

Standards: IEC 601-1,

IEC 645-1, class 4,

medical directive 93/42/EEC

Standard accessories: DD 45 headset, audiogram pad

Power supply: 3 AA batteries (100 hours life time

typically) or optional power supplycord

Dimensions: W x H x D:

22.5 cm x 18 cm x 5.5 cm

Weight: 980 g

Options: Hughson-Westlake test, patient response

button, power supply cord, carrying bag, headset Holmco 8103, TDH 39 or HDA 280 instead of DD 45

For sales and service in your area:



Glenn Johnson 0414 452 007 glenn@hearingcompany.com.au

Specifications are subject to change without notice



MAICO Diagnostic GmbH Salzufer 13/14 10587 Berlin, Germany Tel.: +49 30/70 71 46-50

Fax: +49 30/70 71 46-50 Fax: +49 30/70 71 46-99 E-Mail: export@maico.biz Web: www.maico.biz

